

**NISOTEC 2T NAUTIC**

NISOTEC 2T NAUTIC is a high performance lubricant for the superior protection of all two-stroke gasoline outboard motors. NISOTEC 2T NAUTIC has been specially formulated for use in all water cooled two-stroke outboard engines with or without separate oil tanks. It is recommended for all water cooled outboard motors, including Johnson, Evinrude, Mercury, Chrysler, Suzuki and Yamaha. It is suitable for premixed fuel oil or for direct oil injection systems. Performance Features and benefits:

- Minimum engine deposits and cleaner spark plugs ensures longer engine life and better performance
- Improved lubricity and less wear of engine parts
- Without ring sticking which ensures better compression and easier starting
- Good miscibility with gasoline fuels

**Performance Levels:** NMMA TC-W III

**Characteristics**

<b>Properties</b>	<b>Units</b>	<b>Typical Values</b>	<b>Methods</b>
Colour	-	Blue	Visual
Kinematic Viscosity at 100 <sup>o</sup> C	mm <sup>2</sup> /s	9	SRPS ISO 3104
Flash Point	<sup>o</sup> C	120	SRPS EN ISO 2719
Sulphated ash	%w/w	0,01	SRPS ISO 3987

**Storage and handling instructions**

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight. Recommended storage temperature: max. 40°C

**Packaging**

<b>0.1L</b>	<b>0.25L</b>	<b>0.5L</b>	<b>1L</b>	<b>4L</b>	<b>10L</b>	<b>60L</b>	<b>180KG</b>	<b>850KG</b>	<b>IBC</b>	<b>AC</b>
		X20			X2		X			