

NISOTEC 2T NAUTIC

NISOTEC 2T NAUTIC is a high performance lubricant for the superior protection of all two-stroke gasoline outboard motors. NISOTEC 2T NAUTIC has been specially formulated for use in all water cooled two-stroke outboard engines with or without separate oil tanks. It is recommended for all water cooled outboard motors, including Johnson, Evinrude, Mercury, Chrysler, Suzuki and Yamaha. It is suitable for premixed fuel oil or for direct oil injection systems. Performance Features and benefits:

- Minimum engine deposits and cleaner spark plugs ensures longer engine life and better power
- Improved lubricity, better performance; less ring wear
- Reduced ring sticking ensures better compression; easier starting; better performance
- Longer engine life
- Easy to use

Performance Levels: NISOTEC 2T satisfied and exceeds the international specifications:

International specifications: SRPS ISO 6743-15, ISO 13738-2000, API TC/TD, ISO L-ETC/ETD
OEM Requirements: NMMA TC-W III

Characteristics

Properties	Units	Typical Values	Methods
Colour	-	Blue	Visual
Kinematic Viscosity at 100°C	mm ² /s	9	SRPS ISO 3104
Flash Point	°C	95	SRPS EN ISO 2719
Pour Point	°C	-27	SRPS ISO 3016
Sulphated ash	%	0,01	SRPS ISO 3987

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight. Recommended storage temperature: max. 40°C

Packaging

0.1L	0.25L	0.5L	1L	4L	10L	60L	180KG	850KG	IBC	AC
				X4	X2		X			