

NISOTEC 2T SCOOTER

NISOTEC 2T SCOOTER is a premium quality, semi-synthetic lubricant for 2-stroke motorcycle engines. It is formulated to provide excellent engine protection and cleanliness and reliable control against exhaust system blocking. NISOTEC 2T SCOOTER is suitable for both oil-injection and premix systems. Performance features and benefits:

- Minimum engine deposits and cleaner spark plugs ensures longer engine life and better engine power
- Improved lubricity and better performance
- Reduced ring sticking ensures better compression and easier starting
- Reduced exhaust smoke

Performance Levels: SRPS ISO 6743-15(L-EGD), ISO 13738 (L-EGD), JASO FD, API TC, TISI 1040-2534

Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Colour	-	Red	Visual
Density at 15 ^o C	g/cm ³	0.891	SRPS EN ISO 3675
Kinematic Viscosity at 100 ^o C	mm ² /s	9.5	SRPS ISO 3104
Flash Point	^o C	85	SRPS EN ISO 2719
Pour Point	^o C	-27	SRPS ISO 3016
Sulphated ash	% m/m	0,14	SRPS ISO 3987

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

Packaging

<i>0.1L</i>	<i>0.25L</i>	<i>0.5L</i>	<i>1L</i>	<i>4L</i>	<i>10L</i>	<i>60L</i>	<i>180KG</i>	<i>850KG</i>	<i>IBC</i>	<i>AC</i>
	X20	X20			X2		X			