

NISOTEC 2T SINT

NISOTEC 2T SINT is synthetic oil for ultimate performance and protection of 2-stroke engines. Its advance formula gives superior performance in all 2-stroke engines, even those subjected to the most extreme conditions. NISOTEC 2T SINT is a self-mixing oil containing hydrocarbon diluents. It is blended to the correct viscosity for use in oil injection systems fitted to modern 2-stroke motorcycles engines with oil injection or premix system. Especially recommended for high-performance air cooled 2-stroke engines. Performance features and benefits:

- Improved engine responsiveness compared to mineral oil products
- Extremely low smoke
- Maximum protection against scuffing and ring sticking
- Ultra low exhaust system deposits and outstanding engine cleanliness
- Helps to extend engine life
- Excellent mixing with petrol

Performance Levels: SRPS ISO 6743-15 (ISO-L-EGD), ISO 13738 (L-EGD), JASO-FD, API TC, TISI 1040-2534, ASTM D4682 (grupa III), SAE J 1536 (grupa III), Piaggio Hexagon, Husqvarna 272&372&346, Stihl, Rotax 253

Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Colour	-	Red	Visual
Density	g/cm ³	0.875	SRPS EN ISO 3675
Kinematic Viscosity at 100 ^o C	mm ² /s	9	SRPS ISO 3104
Flash Point	^o C	80	SRPS EN ISO 2719
Pour Point	^o C	-40	SRPS ISO 3016
Sulphated ash	% m/m	0,16	SRPS ISO 3987

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

Packaging

<i>0.1L</i>	<i>0.25L</i>	<i>0.5L</i>	<i>1L</i>	<i>4L</i>	<i>10L</i>	<i>60L</i>	<i>180KG</i>	<i>850KG</i>	<i>IBC</i>	<i>AC</i>
	X20	X20			X2		X			