

## NISOTEC 2T

NISOTEC 2T is economical mineral oil for lubrication of two-stroke gasoline engines with air-cooling. Used for lubrication old generation of motorcycles, motor scooters, agricultural machines, motor saws, pumps and other low capacity engines (typically below 50cm<sup>3</sup>), where extra reduced smoke emission is not required. Apply mixed with fuel, in a ratio recommended by engine manufacturer. Performance features and benefits:

- Good lubrication of engine parts that minimizes wear
- Reduced formation of deposits on spark plugs to protect spark plugs
- Fully and instant mixing with fuel

**Performance Levels:** SRPS ISO 6743-15 (L-EGC), SRPS ISO 13738 (L-EGC), API TC, JASO-FC

### Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Colour	-	Red	Visual
Density at 15°C	g/cm <sup>3</sup>	0.88	ASTM D 4052
Kinematic Viscosity at 100°C	mm <sup>2</sup> /s	9	SRPS ISO 3104
Flash Point	°C	100	SRPS EN ISO 2719
Pour Point	°C	<-18	SRPS ISO 3016
Sulphated ash	% m/m	0.08	SRPS ISO 3987

### Storage and handling instructions

Store in the original container, in dry well ventilated area. Protect from direct atmospheric influences. Follow storing and handling instructions given in SDS.

### Packaging

<i>0.1L</i>	<i>0.25L</i>	<i>0.5L</i>	<i>1L</i>	<i>2L</i>	<i>4L</i>	<i>10L</i>	<i>60L</i>	<i>180KG</i>	<i>IBC</i>	<i>AC</i>
		X20						X		