

NISOTEC 2T

NISOTEC 2T is economical mineral oil for lubrication of two-stroke gasoline engines with air-cooling. Used for lubrication old generation of motorcycles, motor scooters, agricultural machines, motor saws, pumps and other low capacity engines (typically below 50cm³), where reduced smoke emission is not required. Apply mixed with fuel, in a ratio recommended by engine manufacturer. Performance features and benefits:

- Good engine protection and cleanliness
- Good self mixing with leaded and unleaded petrol

Performance Levels: SRPS ISO 6743-15 (ISO-L-EGB), ISO 13738 (L-EGB), JASO-FB

Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Colour	-	Red	Visual
Density at 150C	g/cm ³	0.882	SRPS EN ISO 3675
Kinematic Viscosity at 100°C	mm ² /s	9	SRPS ISO 3104
Flash Point	°C	100	SRPS EN ISO 2719
Pour Point	°C	<-18	SRPS ISO 3016
Sulphated ash	% m/m	0,08	SRPS ISO 3987

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

Packaging

0.1L	0.25L	0.5L	1L	4L	10L	60L	180KG	850KG	IBC	AC
		X20			X2		X			