

NISOTEC 4T MOTO SAE 10W-40

NISOTEC 4T MOTO SAE 10W-40 is high performance, semi synthetic engine oil, for the lubrication of gasoline four-stroke engines of motorcycle and scooter. Specially formulated oil for lubrication systems of motorcycle where engine, gearbox and clutch are integrated providing superior performance.

Provides:

- Engine cleanliness and excellent wear protection
- Fast and smooth gear changing
- Excellent properties in cold weather conditions
- Optimal frictional properties

Performance Levels: JASO MA2, API SL

Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Density at 15°C	g/cm ³	0.871	ASTM D 4052
Kinematic viscosity at 100°C	mm ² /s	14.5	SRPS ISO 3104
Index viscosity	-	150	SRPS ISO 2909
Flash Point, COC	°C	225	SRPS EN ISO 2592
Pour Point	°C	-33	SRPS ISO 3016

Storage and handling instructions

Store in the original container, in dry well ventilated area. Protect from direct atmospheric influences. Follow storing and handling instructions given in SDS.

Packaging

<i>0.1L</i>	<i>0.25L</i>	<i>0.5L</i>	<i>1L</i>	<i>4L</i>	<i>10L</i>	<i>60L</i>	<i>180KG</i>	<i>IBC</i>	<i>AC</i>
			X16						