

## NISOTEC AGRO UNIVERSAL MHT

NISOTEC AGRO UNIVERSAL MHT is a high performance, multi-functional lubricants for most farm equipment application. This STOU lubricant provides good performance in diesel and gasoline engines, transmissions, hydraulics, final drives, and oil-immersed brakes operating in agricultural service. NISOTEC AGRO UNIVERSAL MHT is recommended for use in a wide range of heavy-duty applications and operating environments found in the farming industry. Features and Benefits:

- Reduced wear and long equipment life especially in hydraulic components
- Reduced sludge build-up and high temperature deposits
- Cleaner engines and long engine life
- Improved deposit control

**Performance Levels:** Engine: ACEA E2/E3, API API CF/ SF, MB 228.3/MB 227.1, MAN 271, Transmission: MIL-L-2104D, API GL-4, ZF TE ML 06B&C, Allison C-4, STOU: Massey Ferguson M1139/M1144/11454, John Deere J27C/J20D, Ford M2C159B/C, CaseNew Holland FNH Material82009201/2/3, UTTO: Massey Ferguson M1135/M1143/1145, Ford M2C134D, John Deere J20C

### Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Density at 15 <sup>o</sup> C	g/cm <sup>3</sup>	0.88	SRPS EN ISO 3675
Kinematic viscosity at 100 <sup>o</sup> C	mm <sup>2</sup> /s	15	SRPS ISO 3104
Index viscosity	-	140	SRPS ISO 2909
Flash Point, COC	<sup>o</sup> C	220	SRPS ISO 3016
Pour Point	<sup>o</sup> C	-30	SRPS ISO 2592
TBN	mgKOH/g	9.6	ASTM D 2896

### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight. Recommended storage temperature: max. 40°C

### Packaging

<i>0.1L</i>	<i>0.25L</i>	<i>0.5L</i>	<i>1L</i>	<i>4L</i>	<i>10L</i>	<i>60L</i>	<i>180KG</i>	<i>850KG</i>	<i>IBC</i>	<i>AC</i>
					X2		X			