

## NISOTEC ATF DII

NISOTEC ATF DII is a high performance automatic transmission fluid. NISOTEC ATF DII is fluid recommended for use in automatic transmission systems of GM type. It is also recommended for lubrication of steering systems for cars, commercial and off-road vehicles, torque converter transmissions, hydraulic clutches and other hydraulic systems in which manufacturer demands use of Dexron DII type of fluid. Features and Benefits:

- Longer retention of frictional characteristics under severe operating conditions
- Good low temperature fluidity
- Good high temperature stability to resist lacquer and deposit formation
- Good protection against wear and excellent foam resistance

**Performance Levels:** GM DEXRON IID, ZF TE-ML 03D/04D/14A/17C, VOITH 55.6335 Approved, MB 236.1/236.6/236.7/236.9, MAN 339V1&Z1, ALLISON C-4, CARTEPILLAR TO-2, Volvo 97335

### Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Colour	-	Red	Visual
Density at 15°C	g /cm <sup>3</sup>	0.878	SRPS EN ISO 3675
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	7.0	SRPS ISO 3104
Index viscosity	-	150	SRPS ISO 2909
Dynamic viscosity at -40°C (Brookfield)	mPas	<40 000	ASTM D2983
Flash Point, COC	°C	200	SRPS EN ISO 2592
Pour Point	°C	-45	SRPS ISO 3016

### Storage and handling instructions

Store in the original container, in dry well ventilated area. Protect from direct atmospheric influences. Follow storing and handling instructions given in SDS.

### Packaging

0.1L	0.25L	0.5L	1L	2L	4L	10L	20L	60L	180KG	IBC	AC
			X16			X	X	X	X	X	