

NISOTEC ATF III SINT

NISOTEC ATF III SINT is a high performance synthetic automatic transmission fluid. It is recommended for use in automatic transmission systems in which manufacturer demands use of Dexron IIIH type of fluid of cars and commercial vehicles. It is also recommended for lubrication of steering systems and torque convertor transmissions. Features and Benefits:

- Exceptional low temperature fluidity
- Exceptional thermal and oxidation stability
- Stable viscosity
- Compatibility with sealing materials
- Excellent frictional properties
- Extended drain interval

Performance Levels: GM DEXRON IIIH, Voith 55.6336 Approved, ZF TE-ML 02F/04D/09/14C/16M/17C/20C, MB 236.6, MAN 339V2&Z2, Allison C-4/TES-295, Volvo 97340/97341

Characteristics

Properties	Units	Typical Values	Methods
Color	-	Red	Visually
Density at 15°C	g /cm ³	0.84	SRPS EN ISO 3675
Kinematic viscosity at 100 °C	mm ² /s	7.6	SRPS ISO 3104
Index viscosity, COC	°C	180	SRPS ISO 2909
Dynamic viscosity (Brookfield) at -40 °C	mPas	8000	ASTM D2983
Flush point, COC	°C	235	SRPS EN ISO 2592
Pour Point	°C	-50	SRPS ISO 3016

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct weather conditions. Follow storing and handling instructions given in SDS.

Packaging

0.1L	0.25L	0.5L	1L	4L	10L	60L	175KG	IBC	AC
			X16				X		