

## NISOTEC ATF IIIH

NISOTEC ATF IIIH is a high performance automatic transmission fluid. It is recommended for use in automatic transmission systems in which manufacturer demands use of Dexron III type of fluid. It is also recommended for lubrication of steering systems for cars, commercial and off-road vehicles, torque converter transmissions, hydraulic clutches and other hydraulic systems. Features and Benefits:

- Retains excellent frictional characteristics under severe operating conditions
- Good protection against wear and excellent foam resistance
- Extended drain interval

**Performance Levels:** GM DEXRON IIIH, ZF TE-ML 14A/14B,04D, 16L, 17C, VOITH DIWA 55.6335 (VOITH G 607), MB 236.1/ 236.6, Allison TES 389/Allison C-4, MAN 339F, Volvo 97341, Caterpillar TO-2

### Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Color	-	Red	Visual
Density at 15°C	g /cm <sup>3</sup>	0.853	EN ISO 3675
Kinematic viscosity at 100 °C	mm <sup>2</sup> /s	7.2	ISO 3104
Dynamic viscosity (Brookfield) at -40 °C	mPas	18 000	ASTM D2983
Flash Point, COC	°C	210	EN ISO 2592
Pour Point, max	°C	-45	ISO 3016
Copper corrosion, 150°C, 3h	-	1a	ISO 2160

### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight. Recommended storage temperature: max. 40°C

### Packaging

<i>0.1L</i>	<i>0.25L</i>	<i>0.5L</i>	<i>1L</i>	<i>4L</i>	<i>10L</i>	<i>60L</i>	<i>180KG</i>	<i>850KG</i>	<i>IBC</i>	<i>AC</i>
			X16				X			