

NISOTEC ATF IIIH

NISOTEC ATF IIIH is a high performance automatic transmission fluid. It is recommended for use in automatic transmission systems in which manufacturer demands use of Dexron III type of fluid. It is also recommended for lubrication of steering systems for cars, commercial and off-road vehicles, torque converter transmissions, hydraulic clutches and other hydraulic systems. Features and Benefits:

- Retains excellent frictional characteristics under severe operating conditions
- Good protection against wear and excellent foam resistance
- Extended drain interval

Performance Levels: Mercon, GM DEXRON IIIH, ZF TE-ML 03D/04D/05L/09/14B/17C, VOITH H55.6335, MB 236.1/ 236.5/236.6/236.9, Allison TES 389/Allison C-4, MAN 339V1&Z1, Volvo 97341

Characteristics

Properties	Units	Typical Values	Methods
Color	-	Red	Visual
Density at 15°C	g /cm ³	0.86	EN ISO 3675
Kinematic viscosity at 100 °C	mm ² /s	7.4	ISO 3104
Dynamic viscosity (Brookfield) at -40 °C	mPas	11 000	ASTM D2983
Index viscosity, COC	°C	170	ISO 2909
Pour Point, max	°C	-45	ISO 3016
Copper corrosion, 150°C, 3h	-	1a	ISO 2160

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight. Recommended storage temperature: max. 40°C

Packaging

0.1L	0.25L	0.5L	1L	4L	10L	60L	180KG	850KG	IBC	AC
			X16				X			