

## NISOTEC ATF SUFFIX A

NISOTEC ATF Suffix A is an economic automotive transmission fluid. It is recommended for some automatic and manual transmissions in passenger cars and light duty trucks as well as for power steering systems. It is also suitable for hydraulic systems in farm equipment and other installations having similar fluid requirements. Features and Benefits:

- Good low temperature fluidity
- Good high temperature stability to resist lacquer and deposit formation
- Good protection against wear and excellent foam resistance

**Performance Levels:** GM DEXRON Type A Suffix A

### Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Colour	-	Red	Visual
Density at 15°C	g/cm <sup>3</sup>	0.875	SRPS EN ISO 3675
Kinematic viscosity at 100 °C	mm <sup>2</sup> /s	7.0	SRPS ISO 3104
Dynamic viscosity (Brookfield), -40 °C	mPas	65 000	ASTM D2983
Flash Point, COC	°C	200	SRPS EN ISO 2592
Pour Point	°C	-42	SRPS ISO 3016
Copper corrosion, 150°C, 3h	class	1a	SRPS ISO 2160

### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight. Recommended storage temperature: max. 40°C

### Packaging

0.1L	0.25L	0.5L	1L	4L	10L	60L	180KG	850KG	IBC	AC
			X16				X			