

NISOTEC AUTOGAS SAE 15W- 40

NISOTEC AUTOGAS SAE 15W-40 is a special, high-quality, multigrade engine oil, for lubrication of gasoline engines of passenger vehicles that use LPG (LPG-Liquefied Petroleum Gas) or petrol as fuel. It is designed for passenger and light commercial vehicles, classic design that operates in moderate conditions. Suitable for normal oil change periods. Provides:

- Wear protection
- Engine cleanliness
- Stable viscosity at high temperatures

Performance Levels: API SL/CF, ACEA A3/B3

Characteristics

Properties	Units	Typical Values	Methods
Density at 15°C	kg/m ³	878	SRPS EN ISO 3675
Kinematic viscosity at 100°C	mm ² /s	14	SRPS ISO 3104
Apparent viscosity, CCS na -20°C	mPa s	6400	ASTM D5293
Index viscosity	-	140	SRPS ISO 2909
Flash Point, COC	°C	220	SRPS EN ISO 2592
Pour Point	°C	-27	SRPS ISO 3016
HTHS viscosity (150°C, 10 ⁻⁶ s ⁻¹)	mPas	4.1	ASTM D 4683
Foaming, max Seq. I/ II/ III	mL/mL	10/0, 20/0, 10/0	SRPS ISO 6247

Storage and handling instructions

Store in the original container in cold, dry, properly ventilated area. Follow storing and handling instructions given in SDS.

Packaging

0.1L	0.25L	0.5L	1L	4L	10L	60L	180KG	IBC	AC
			X16	X4			X		