

NISOTEC AUTOGAS SAE 15W- 40

NISOTEC AUTOGAS SAE 15W-40 is a special, high-quality, multigrade motor oil, for lubrication of gasoline engines of passenger vehicles that use LPG (LPG-Liquefied Petroleum Gas) or petrol as fuel. It is designed for passenger and light commercial vehicles, classic design that operates in moderate conditions. Suitable for normal oil change periods. In relation to the standard mineral engine oil provides:

- Better wear protection
- Excellent engine cleanliness
- Better oxidation stability at high temperatures

Performance Levels: API SL/CF, ACEA A3/B3-04

Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Density at 15°C	g/cm ³	0.88	SRPS EN ISO 3675
Kinematic viscosity at 100°C	mm ² /s	14	SRPS ISO 3104
Apparent viscosity, CCS na -20°C	mPa s	6400	ASTM D5293
Index viscosity	-	140	SRPS ISO 2909
Flash Point, COC	°C	220	SRPS EN ISO 2592
Pour Point	°C	-27	SRPS ISO 3016
Base Number	mgKOH/g	7	SRPS ISO 3771
Foaming, max Seq. I/ II/ III	mL/mL	10/0, 20/0, 10/0	SRPS ISO 6247

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight. Recommended storage temperature: max. 40°C

Packaging

<i>0.1L</i>	<i>0.25L</i>	<i>0.5L</i>	<i>1L</i>	<i>4L</i>	<i>10L</i>	<i>60L</i>	<i>180KG</i>	<i>850KG</i>	<i>IBC</i>	<i>AC</i>
			X16	X4			X			