

## NISOTEC AUTOLINE PS SAE 10W-40

NISOTEC AUTOLINE PS SAE 10W-40 is universal semi synthetic, multigrade, high-performance engine oil intended for lubricating all types of modern gasoline and diesel engines of passenger cars and light commercial vehicles. Especially adapted to the requirements of the engine with direct injection. It is recommended for gasoline engines with or without catalytic converters and diesel engines with direct injection, with or without turbocharger and common rail. It is designed for use in the most severe climatic conditions for all types of urban, inter-city driving, and driving on motorways.

Features and benefits:

- Outstanding wear protection
- Excellent engine cleanliness
- Outstanding high temperature protection
- Low temperature protection and easy winter starting

**Performance Levels:** API SL/CF, ACEA A3/B3-16, ACEA A3/B4-16, MB-229.1, VW 501.01/505.00

### Characteristics

Properties	Units	Typical Values	Methods
Density at 15°C	kg/m <sup>3</sup>	874	SRPS EN ISO 3675
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	14.5	SRPS ISO 3104
Apparent viscosity at -25°C (CCV)	mPas	6250	ASTM D5293
Index viscosity	°C	150	SRPS EN ISO 2592
Flash Point, COC	°C	220	SRPS ISO 3016
Pour Point	mgKOH/g	-33	SRPS ISO 3771
TBN	%w/w	10	SRPS ISO 3987
Evaporation loss (Noack)	%w/w	10	ASTM D5400
Foaming, max seq I/ II/ III	mL/mL	10/0, 50/0, 10/0	SRPS ISO 6247

### Storage and handling instructions

Store in the original container in cold, dry, properly ventilated area. Follow storing and handling instructions given in SDS.

### Packaging

0.1L	0.25L	0.5L	1L	2L	4L	10L	60L	180KG	IBC	AC
			X16		X4		X	X	X	