

## NISOTEC CLEANER

NISOTEC CLEANER is general purpose degreasing fluid cleaner for removal of oil, grease, dirt and soot from a variety of industrial surfaces by immersion and hand application. It is efficient cold degreasing and cleaning product based on petroleum solvents and emulsifiers. It emulsifies with water and creates stable emulsion. It efficiently dissolves all deposits of petroleum and its derivatives, waxy, resinous and similar residues. It is efficient in application for de-preservation of parts and equipment from all protective coatings made on the basis of petroleum derivatives. It is recommended for use as concentrate, in delivered form or diluted with water as emulsion or diluted with petroleum or other petroleum solvents. It does not have harmful effects on lacquer, dye, rubber and sealing material. It does not contain chlorinated hydrocarbons. Features and Benefits:

- Provides good penetration into moulds and parting surfaces
- Easy to apply via brushing, swabbing or conventional spray systems
- Competitively priced

**Performance Levels:** In-House specification SP-04.07.28-558

### Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Density at 15°C	g/cm <sup>3</sup>	0.88	SPRS EN ISO 3675
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	4.5	SRPS ISO 3104
Flash Point, COC	°C	85	SRPS EN ISO 2719
pH value of 5% emulsion	-	8.5	pH-meter

### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight. Recommended storage temperature: max. 40°C

### Packaging

<i>0.1L</i>	<i>0.25L</i>	<i>0.5L</i>	<i>1L</i>	<i>4L</i>	<i>10L</i>	<i>60L</i>	<i>175KG</i>	<i>850KG</i>	<i>IBC</i>	<i>AC</i>
			X16		X2		X			