

## NISOTEC DIZEL S-3 SAE 15W-40

NISOTEC DIZEL S-3 SAE 15W-40 are economical, multigrade mineral motor oils intended for lubrication four-stroke diesel engine of lorries, buses, agricultural, construction and similar machines old construction, with and without turbo group, working in moderate and severe conditions and with varying workloads. Features and Benefits:

- Reliable engine operation
- High temperature wear protection
- Keep engine clean

**Performance Levels:** API CD/SF, MIL L-2104D

### Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Density at 15°C	g/cm <sup>3</sup>	0.88	SRPS EN ISO 3675
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	15	SRPS ISO 3104
Index viscosity	-	130	SRPS ISO 2909
Apparent viscosity, CCS, at -20°C	mPa.s	6850	ASTM D 5293
Flash Point, COC	°C	225	SRPS EN ISO 2592
Pour Point	°C	-24	SRPS ISO 3016
Total Base No.	mgKOH/g	10	SRPS ISO 3771
Foaming, max seq I/ II/ III	mL/mL	0/0; 50/0; 0/0	SRPS ISO 6247

### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight. Recommended storage temperature: max. 40°C

### Packaging

<i>0.1L</i>	<i>0.25L</i>	<i>0.5L</i>	<i>1L</i>	<i>4L</i>	<i>10L</i>	<i>60L</i>	<i>180KG</i>	<i>850KG</i>	<i>IBC</i>	<i>AC</i>
			X16	X4	X2		X			