

NISOTEC DIZEL S-3 SAE 30, SAE-40

NISOTEC DIZEL S-3 SAE 30 and SAE-40 are economical, monograde mineral motor oils intended for lubrication four-stroke diesel engine lorries, buses, agricultural, construction and similar machines old construction, with and without turbo group, working in moderate and severe conditions and with varying workloads. Can be used for lubrication of the compressor, less loaded gear, hydraulic devices that allow the use of monograde motor oil. Grade SAE 40 is used only for the period from mid-spring to mid-autumn, i.e. during the summer climate. Features and Benefits:

- Reliable engine operation
- High temperature wear protection
- Keep engine clean

Performance Levels: API CD/SF, MIL L-2104D

Characteristics

Properties	Units	Typical Values		Methods
		SAE 30	SAE 40	
Density at 15°C	g/cm ³	0.88	0.89	SRPS EN ISO 3675
Kinematic viscosity at 100°C	mm ² /s	11	15	SRPS ISO 3104
Index viscosity	-	95	90	SRPS ISO 2909
Flash Point, COC	°C	220	230	SRPS ISO 3016
Pour Point	°C	-24	-15	SRPS ISO 3771
Total Base No.	mgKOH/g	10	10	SRPS ISO 6247
Foaming, max seq I/ II/ III	mL/mL	0/0; 20/0; 0/0		SRPS ISO 6247

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight. Recommended storage temperature: max. 40°C

Packaging

0.1L	0.25L	0.5L	1L	4L	10L	60L	180KG	850KG	IBC	AC
			X16	X4	X2		X			