

NISOTEC FAVORIT E9 SAE 10W-40

NISOTEC FAVORIT E9 SAE 10W-40 is synthetic super high performance diesel engine oil for lubrication modern, high performance, low emissions engines of commercial vehicle like city and intersity traffic. The new advanced additive system has been expertly engineered to help prolong the life and maintain the efficiency of emission reduction systems such as the Diesel Particulate Filter (DPF). Features and Benefits:

- Outstanding control of high temperature deposits
- Excellent protection against wear
- Good viscosity control
- Good pumpability
- Enhanced protection of exhaust systems

Performance Levels: ACEA E9-12, API CJ-4/CI-4+/CI-4/CH-4/SN, MB 228.31, MAN M3575, MTU Type 2.1, Volvo VDS-4, Mack EO-O Premium Plus-07, Renault Trucks VI RLD-3, Cummins CES 20081, Detroit Diesel DDC 93K218, Caterpillar ECF-3/ECF-2/ECF-1-a, Deutz DQC III-10LA

Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Density at 15°C	g/cm ³	0,865	SRPS EN ISO 3675
Kinematic viscosity at 100°C	mm ² /s	14.5	SRPS ISO 3104
Apparent viscosity, CCS at 25°C	mPa.s	5900	ASTM D 5293
Index viscosity	-	155	SRPS ISO 2909
Flash Point, COC	°C	220	SRPS EN ISO 2592
Pour Point	°C	-33	SRPS ISO 3016
Sulphate Ash, max.	% m/m	1.0	SRPS ISO 3987
Total Base No.	mgKOH/g	8	SRPS ISO 3771
Foaming, seq I/ II/ III, max.	mL/mL	10/0; 20/0; 10/0	SRPS ISO 6247

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct weather conditions. Follow storing and handling instructions given in SDS.

Packaging

<i>0.1L</i>	<i>0.25L</i>	<i>0.5L</i>	<i>1L</i>	<i>4L</i>	<i>10L</i>	<i>60L</i>	<i>180KG</i>	<i>IBC</i>	<i>AC</i>
					X2		X	X	