

## NISOTEC GREASE Ca 2

NISOTEC GREASE Ca 2 is grease with Ca soap as thickener intended for the lubrication of bearings requiring water resistant greases. It is designated for the lubrication of industrial and agriculture equipments bearings, low speed, working under medium loadings and temperatures. The allowed operating temperatures range is from -25 to +60°C.

- Provide excellent protection against rust and corrosion in the presence of water and high humidity conditions

**Performance Levels:** ISO 6743-9: ISO-L-XBAHA 2, DIN 51502: K 2 C-25

### Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
NLGI grade		2	ASTM D217
Visual appearance	-	green	Visual
Penetration at 25 <sup>0</sup> C	0.1 mm	275	SRPS ISO 2137
Dropping point	<sup>0</sup> C	90	SRPS ISO 2176
Emcor Test	merit	0-40	DIN 51807-1
FB EP Test - Weld point	N	2150	ASTM D 2596

### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

### Packaging

<i>EUROCARD. 400G</i>	<i>400G</i>	<i>800G</i>	<i>4KG</i>	<i>20KG</i>	<i>180KG</i>
		X	X	X	X