

NISOTEC GREASE Graphite 2 EP

NISOTEC GREASE Graphite 2 EP is grease intended for the lubrication bearings operating under high and shock loads. The operating temperature range is from -20 to 120⁰C. Benefits:

- Stability against shock loads
- Exelent protection agains corrosion and wear
- Resistance to water

Performance Levels: NLGI 2, ISO 6743-9: ISO-L-XBCHB-2, DIN 51502: KPF 2K-20

Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
NLGI grade		2	ASTM D217
Visual apperance	-	Dark grey	Visual
Penetration at 25 ⁰ C	0.1 mm	280	SRPS ISO 2137
Dropping point, min.	⁰ C	190	SRPS ISO 2176
FB EP Test Wear scar diameter	mm	0.5	ASTM D 2266
FB EP Test Weld point	N	3150	ASTM D 2596

Storage and handling instructions

Store in the original container, in dry well ventilated area. Protect from direct atmospheric influences. Follow storing and handling instructions given in SDS.

Packaging

<i>EUROCARD. 400G</i>	<i>400G</i>	<i>800G</i>	<i>4KG</i>	<i>20KG</i>	<i>180KG</i>
		X	X	X	X