

NISOTEC GREASE Li 00 EP

NISOTEC GREASE Li 00 EP is multipurpose semi-fluid antifriction EP lithium 12-hydroksystearate based grease intended for the lubrication and sealing centralized lubrication systems in vehicles, gear and other mechanisms operated in the open. Temperature range is from -30 to 100°C.

- Provide very good mechanical stability
- Provide excellent protection against rust and corrosion
- Stable under high speed
- Stable under high pressures and/or shock loads

Performance Levels: NLGI 00, ISO 6743/9: ISO-L-XCBHB-00, DIN 51502: GP 00 G-30

Characteristics

Properties	Units	Typical Values	Methods
NLGI grade		00	ASTM D217
Visual appearance	-	Yellow brown	Visual
Penetration at 25°C, 0.1 mm	g/cm ³	415	SRPS ISO 2137
Dropping point, °C, min.	mm ² /s	150	SRPS ISO 2176
Emcor Test	merit	0:0	DIN 51802
FB EP Test Weld point	N	3150	ASTM D 2596

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight. Recommended storage temperature: max. 40°C.

Packaging

EUROCARD. 400G	400G	800G	4KG	20KG	180KG
		X	X	X	X