

### **NISOTEC GREASE Li 00 EP**

NISOTEC GREASE Li 00 EP is multipurpose semi-fluid antifriction EP lithium 12-hydroksystearate based grease intended for the lubrication and sealing centralized lubrication systems in vehicles, gear and other mechanisms operated in the open. Temperature range is from -30 to 100<sup>0</sup>C.

- Provide very good mechanical stability
- Provide excellent protection against rust and corrosion
- Stable under high speed
- Stable under high pressures and/or shock loads

**Performance Levels:** NLGI 00, ISO 6743-9: ISO-L-XCBHB-00, DIN 51502: GP 00 G-30

#### **Characteristics**

<b>Properties</b>	<b>Units</b>	<b>Typical Values</b>	<b>Methods</b>
NLGI grade		00	ASTM D217
Visual appearance	-	Yellow brown	Visual
Penetration at 25 <sup>0</sup> C	0.1 mm	415	SRPS ISO 2137
Dropping point, min.	<sup>0</sup> C	150	SRPS ISO 2176
Emcor Test	merit	0:0	DIN 51802
FB EP Test Weld point	N	3150	ASTM D 2596

#### **Storage and handling instructions**

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

#### **Packaging**

<b>EUROCARD. 400G</b>	<b>400G</b>	<b>800G</b>	<b>4KG</b>	<b>20KG</b>	<b>180KG</b>
		X	X	X	X