

NISOTEC GREASE Li LONG LIFE

NISOTEC GREASE Li 1 LONG LIFE is multipurpose antifriction lithium 12-hydroxystearate based grease with EP additives and long lasting performance. It is intended for the lubrication plain and rolling bearings and other mechanism operated under high pressures, in the temperature range from -30 to 130°C. Benefits:

- Protect metal surfaces against rust and corrosion
- Very good oxidation and water resistance
- Stable under high pressures and/or shock loads

Performance Levels: NLGI 1/2; ISO 6743-9: ISO-L-XCCHB-1/2, DIN 51502-KP 1/2K-30

Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>		<i>Methods</i>
NLGI grade	-	1	2	ASTM D217
Visual appearance	-	Yellow brown		Visual
Penetration at 25°C	0.1 mm	320	280	SRPS ISO 2137
Dropping point, min.	°C	188	195	SRPS ISO 2176
Emcor Test	merit	0:0		DIN 51802
FB EP Test - Weld point	N	3150		ASTM D 2596
FB Wear Test - Scar diameter	mm	0.5		ASTM D2266

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight. Recommended storage temperature: max. 40°C.

Packaging

<i>EUROCARD. 400G</i>	<i>400G</i>	<i>800G</i>	<i>4KG</i>	<i>20KG</i>	<i>180KG</i>
				X	X