

NISOTEC GREASE Li MoS 2 EP

NISOTEC GREASE Li MoS 2 EP is multipurpose antifriction lithium 12-hydroksystearate based grease with addition 3% molybdenum disulphide (MoS₂). MoS₂ ensure protection against high and shock loads specific for industrial and agricultural machinery. The operating temperature range is from -20 to 100^oC. Benefits:

- High temperatures and water resistance grease
- Exelent protection against rust and corrosion
- Resistance to oxidation

Performance Levels: NLGI 2, ISO 6743-9: ISO-L-XBCHB-2, DIN 51502: KPF 2K-20

Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
NLGI grade		2	ASTM D217
Visual apperance	-	Dark grey	Visual
Penetration at 25 ^o C	0.1 mm	280	SRPS ISO 2137
Dropping point, min.	^o C	190	SRPS ISO 2176
Emcor Test	merit	0:0	DIN 51802
FB EP Test - Weld point	N	3150	ASTM D 2596

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight. Recommended storage temperature: max. 40^oC.

Packaging

<i>EUROCARD. 400G</i>	<i>400G</i>	<i>800G</i>	<i>4KG</i>	<i>20KG</i>	<i>180KG</i>
				X	X