

NISOTEC GREASE Li 2 PELLET

NISOTEC GREASE Li 2 PELLET is premium quality grease intended for the lubrication of bearings of equipment for production wooden pellets.

Provides:

- Reliable operating on high temperatures
- Resistance to high pressures and loading
- Very efficient protection against wear and rust in presence of water

Performance Levels: ISO 6743-9: ISO L-XBDEB 2, DIN 51502: KP 2 N-20

Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
NLGI grade		2	ASTM D217
Colour	-	Yellow brown	Visually
Penetration at 25 ⁰ C	0.1 mm	275	SRPS ISO 2137
Dropping point	⁰ C	225	SRPS ISO 2176
Cu corrosion test (100 ⁰ C, 24h)	merit	1a	SRPS ISO 2160
FB EP Test - Weld point	N	3150	ASTM D 2596
FB Wear Test - Scar diameter	mm	0.45	ASTM D2266
Flow Pressure (-20 ⁰ C)	mbar	780	DIN 51805

Storage and handling instructions

Store in the original container, in good ventilated area. Protect from direct atmospheric influences. Follow storing and handling instructions given in SDS.

Packaging

<i>EUROCARD. 400G</i>	<i>400G</i>	<i>800G</i>	<i>4KG</i>	<i>20KG</i>	<i>180KG</i>
		X	X	X	X