

NISOTEC GREASE Li Complex 2 EP

NISOTEC GREASE Li Complex 2 EP is premium quality grease with Li-complex soap as thickener and EP additives. It is intended for the lubrication of bearings and couplings embedded in vehicle, construction and agriculture machinery, as well as electric motor bearings. Can be used for the lubrication of plain and roller bearings in most industrial applications. Provides:

- Lubrication in conditions of high load and higher temperature.
- Very good metal surfaces protection against rust and corrosion in presence of water

Performance Levels: NLGI 2, ISO 6743-9: ISO L-XCDIB-2, DIN 51502: KP 2 N-30, ASTM D 4950 GC-LB

Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
NLGI grade		2	ASTM D217
Colour	-	Red	Visual
Base oil viscosity (40 ⁰ C)	mm ² /s	220	SRPS ISO 3104
Penetration at 25 ⁰ C	0.1 mm	280	SRPS ISO 2137
Dropping point, min.	⁰ C	260	SRPS ISO 2176
Cu corosion test (100 ⁰ C, 24h)	merit	1	SRPS ISO 2160
FB EP Test - Weld point	N	3150	ASTM D 2596

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

Packaging

<i>EURO CART. 400G</i>	<i>400G</i>	<i>800G</i>	<i>4KG</i>	<i>20KG</i>	<i>180KG</i>
		X	X	X	X