

NISOTEC GREASE TEMP 2 EP

NISOTEC GREASE TEMP 2 EP is multipurpose premium quality grease with EP additives, intended for the lubrication bearings operated under high temperature to 180, shortly up to 200°C. Provides:

- Excelent lubrication in high temperatures conditions
- Excelent lubrication in high pressure conditions
- Very good oxidation resistance
- Very good metal surfaces protection against rust and corrosion in high humidity conditions

Performance Levels: NLGI2; ISO 6743-9: ISO-L-XBFB-2, DIN 51502: KP 2R -20

Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
NLGI grade		2	ASTM D217
Visual apperance	-	Yellow brown	Visual
Penetration at 25°C	0.1 mm	280	SRPS ISO 2137
Dropping point, min.	°C	300	SRPS ISO 2176
Cu corrosion test (100°C, 24h)	merit	1	SRPS ISO 2160
Emcor Test (rust protection)	merit	1:1	DIN 51802
FB EP Test - Weld point	N	3150	ASTM D 2596
FB Wear Test - Wear Scar Diametar	mm	0.5	ASTM D2266

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

Packaging

<i>EURO CART. 400G</i>	<i>400G</i>	<i>800G</i>	<i>4KG</i>	<i>20KG</i>	<i>180KG</i>
X		X	X	X	X