

NISOTEC GUM 700

NISOTEC GUM 700 is mineral naphthenic process oil. It is used in rubber industry as a softener in the production of tyres and other rubber products. Features and Benefits:

- Good compatibility with tyre compounds
- Meet healthy demands towards PAH content
- Improve workability

Performance Levels: In-House specification; SRPS ISO 6743-10 (L-Y)

Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Density at 15 ^o C	g/cm ³	0,942	SRPS EN ISO 3675
Color	-	8	SRPS ISO 2049
Kinematic viscosity at 40 ^o C	mm ² /s	670	SRPS ISO 3104
Kinematic viscosity at 100 ^o C	mm ² /s	28	SRPS ISO 3104
Flash point, PM	^o C	220	SRPS EN ISO 2719
Pour point	^o C	- 15	SRPS ISO 3016
Sulphur content	%	0,5	SRPS ISO 8754
Aniline Point	^o C	90	ASTM D611
Neutralization No	mgKOH/g	0.6	SRPS ISO 6619
PCA content, max.	%	3	IP 346

Storage and handling instructions

Store in the original container or reservoir in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

Packaging

<i>0.1L</i>	<i>0.25L</i>	<i>0.5L</i>	<i>1L</i>	<i>4L</i>	<i>10L</i>	<i>60L</i>	<i>180KG</i>	<i>850KG</i>	<i>AC</i>
							X	X	X