

NISOTEC K2

NISOTEC K2 is a hydraulic brake fluid typically used for aftermarket applications. NISOTEC K-2 is designed for use where a DOT 3 Motor Vehicle Brake Fluid is recommended by the motor vehicle manufacturer. NISOTEC K2 is Brake fluid for hydraulic brake and clutch systems with a boiling point of at least 250 °C. Features and Benefits:

- Excellent corrosion protection for ferrous and nonferrous metals.
- High thermal stability

Performance Levels: ISO 4925, SAE J1703, US FMVSS 116 DOT 3, SRPS H.Z2.100 tip 1

Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Density at 15 ^o C	g/cm ³	1.06	ASTM D 4052
Equilibrium Reflux Boiling Point, Dry min	^o C	230	SRPS H.Z8.062
Wet Equilibrium Reflux Boiling Point , min.	^o C	140	SRPS H.Z8.063
Kinematic viscosity -40 ^o C, min.	mm ² /s	1500	SRPS ISO 3104
Kinematic viscosity at 100 ^o C, min.	mm ² /s	1.5	SRPS ISO 3104
pH – Value	-	7.0 – 11.5	SRPS H.Z8.064

Storage and handling instructions

NISOTEC K2 should be stored in its original container until use. Brake fluids are hygroscopic by nature. Containers should be kept sealed to prevent the absorption of moisture. NISOTEC K2 has a shelf life of at least three years when stored in original closed, airtight containers at temperatures of maximum 40 °C.

Packaging

<i>0.1L</i>	<i>0.25L</i>	<i>0.5L</i>	<i>1L</i>	<i>4L</i>	<i>10L</i>	<i>60L</i>	<i>210KG</i>	<i>850KG</i>	<i>IBC</i>	<i>AC</i>
		X20								