

NISOTEC LONG LIFE SAE 20W-60

NISOTEC LONG LIFE SAE 20W-60 is special, multigrade mineral engine oil, for the lubrication of four-stroke gasoline and diesel engines passenger cars and vans that have crossed many miles. Optimal formulation and viscosity grade SAE 20W-60 guarantees good lubrication and wear protection as well as reduced oil consumption. Performance Features and Benefits:

- Reliable engine operation under normal service conditions
- Effective rust and corrosion protection
- Effective wear protection

Performance Levels: API SL/CF, ACEA A2/B3

Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Density at 15°C	g/cm ³	0.894	SRPS EN ISO 3675
Kinematic viscosity at 100°C	mm ² /s	22.5	SRPS ISO 3104
Apparent viscosity, CCV at -15°C	mPa s	9200	ASTM D5293
Index viscosity	-	130	SRPS ISO 2909
Flash Point, COC	°C	230	SRPS EN ISO 2592
Pour Point	°C	-21	SRPS ISO 3016
Base Number	mgKOH/g	7.5	SRPS ISO 3771
Foaming, max seq I/ II/ III	mL/mL	10/0, 50/0, 10/0	SRPS ISO 6247

Storage and handling instructions

Store in the original container and tanks away from direct atmospheric influences. Follow storing and handling instructions given in SDS.

Packaging

<i>0.1L</i>	<i>0.25L</i>	<i>0.5L</i>	<i>1L</i>	<i>2L</i>	<i>4L</i>	<i>10L</i>	<i>60L</i>	<i>180KG</i>	<i>IBC</i>	<i>AC</i>
			X16		X4	X2		X		