

## NISOTEC MOTOR OIL SF SAE 15W-40

NISOTEC MOTOR OIL SF SAE 15W-40 is an economical, multigrade, mineral motor oil used for lubrication four-stroke gasoline engines passenger cars of the old generation where SF/CD specification is recommended. It is suitable for use in normal driving in moderate climate condition. Suitable for normal oil change periods. Motor protection under normal service conditions. Performance Features and benefits:

- Reliable engine operation under driving condition
- Good resistance to thermal and oxidative degradation
- Motor protection under normal service conditions

**Performance Levels:** API SF/ CD, Zastava St.9.55535 (1990)

### Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Density at 15°C	g/cm <sup>3</sup>	0.880	SRPS EN ISO 3675
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	14.5	SRPS ISO 3104
Apparent viscosity, CCS na -20°C,	mPa s	6950	ASTM D5293
Index viscosity	-	135	SRPS ISO 2909
Flash Point, COC	°C	215	SRPS EN ISO 2592
Pour Point	°C	-24	SRPS ISO 3016
Base Number	mgKOH/g	7	SRPS ISO 3771
Evaporation loss NOACK-	%	15	ASTM D5800
Foaming, max Seq I/ II/ III	mL/mL	10/0, 20/0, 10/0	SRPS ISO 6247

### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight. Recommended storage temperature: max. 40°C

### Packaging

0.1L	0.25L	0.5L	1L	4L	10L	60L	180KG	850KG	IBC	AC
			X16	X4			X			