

NISOTEC SUPER SAE 30

NISOTEC SUPER SAE 30 is monograde engine oil designed using high performance mineral base oils and advanced additive system to provide a higher level of performance. It is recommended for commercial vehicles diesel engine operating in moderate and severe conditions for both on and off-highway applications. Features and Benefits:

- Reliable engine operation
- Reduced engine wear
- Keep engine clean without sludge and deposits – longer engine life

Performance Levels: API CF-4/CF/SG, ACEA E2, MB 228.0, MAN M270

Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Density at 15°C	g/cm ³	0.88	SRPS EN ISO 3675
Kinematic viscosity at 100°C	mm ² /s	12	SRPS ISO 3104
Index viscosity	-	98	SRPS ISO 2909
Flash Point, COC	°C	230	SRPS EN ISO 2592
Pour Point	°C	-21	SRPS ISO 3016
Total Base No.	mgKOH/g	11	SRPS ISO 3771
Foaming, max seq I/ II/ III	mL/mL	0/0; 50/0; 0/0	SRPS ISO 6247

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight. Recommended storage temperature: max. 40°C

Packaging

0.1L	0.25L	0.5L	1L	4L	10L	60L	180KG	850KG	IBC	AC
			X16	X4	X2		X			