

NISOTEC TERMOL

NISOTEC TERMOL is mineral based heat transfer oil. It is a non-corrosive heat transfer fluid that is formulated to provide fast and efficient heat transfer when used in a closed system application with expansion tank temperatures up to 315°C. Performance Features and benefits:

- High thermal and oxidative stability. These results in the product having resistance to cracking, carbon, sludge, varnish and lacquer formation during high temperature operation
- High flash and fire points
- High thermal efficiency for rapid and efficient transfer of heat
- Long service life for proven trouble-free operation

Performance Levels: SRPS ISO 6743-12 (L-QC), DIN 51522

Characteristics

Properties	Units	Typical Values		Methods
		VG 32	VG 100	
Density at 15°C	g/cm ³	0.87	0.88	EN ISO 3675
Kinematic Viscosity at 40°C	mm ² /s	32	100	ISO 3104
Flash Point, COC	°C	210	220	EN ISO 2592
Copper corrosion (100°C/3h)	Degree	Class 1		SRPS ISO 3016

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight. Recommended storage temperature: max. 40°C

Packaging

0.1L	0.25L	0.5L	1L	4L	10L	60L	180KG	850KG	IBC	AC
					X2		X			