

## NISOTEC TESTEROL

NISOTEC TESTEROL is chain-saw lubricating oil. It is a reliable lubricant for hand chain-saws that are primarily used for logging and chopping (e.g. Stihl, Husqvarna, Bosch, Black & Decker etc). NISOTEC TESTEROL is intended for lubricating all types of chain saws used for woodworking in severe conditions at high temperatures, in the presence of water, dust and mud. It should not be used for making the fuel mixture for operation of chainsaws for which the used oil for two stroke engines. Features and Benefits:

- The product beneficially decreases the friction temperature of the chain elements operating in the range of adverse combined friction and reduces wear of the chain elements, teeth and guiding plates.
- High antiwear properties
- Good adhesion
- Excellent anti-corrosion properties
- Effective separation of water
- Long life of motor saw chains

**Performance Levels:** ISO-L-AC, Manufacturing specification SP-04.07.28-306

### Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Density at 15 <sup>o</sup> C	kg/cm <sup>3</sup>	0,91	SRPS EN ISO 3675
Kinematic viscosity at 40 <sup>o</sup> C	mm <sup>2</sup> /s	98	SRPS ISO 3104
Flash Point, COC	<sup>o</sup> C	220	SRPS EN ISO 2592
Pour Point	<sup>o</sup> C	-21	SRPS ISO 3016
Copper corossion , 3h, 100 °C	ocena	1a	SRPS ISO 2160

### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight. Recommended storage temperature: max. 40°C

### Packaging

<i>0.1L</i>	<i>0.25L</i>	<i>0.5L</i>	<i>1L</i>	<i>4L</i>	<i>10L</i>	<i>60L</i>	<i>180KG</i>	<i>850KG</i>	<i>IBC</i>	<i>AC</i>
			X16	X4	X2		X			