

NISOTEC TRAKTOL 80

NISOTEC TRAKTOL 80 is universal mineral based oil for lubrication of the tractor transmission and hydraulic systems (UTTO). It is intended for lubricating hydraulic and transmission, as well as cooling and lubrication of wet brakes of tractors and other agricultural and construction machinery, where the manufacturer recommends using a UTTO lubricants. Features and Benefits:

- Good lubrication and wear protection of all moving parts in all service conditions
- Excellent filterability even in the presence of water
- Controlled friction with wet brakes, which enables safe braking without the noise and vibration
- Good compatibility with sealing elements

Performance Levels: API GL-4, John Deere JDM J20C, Ford M2C86-B/C, Massey Ferguson M1135, Caterpillar TO-2

Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Density	kg/cm ³	0,88	SRPS EN ISO 3675
Kinematic viscosity at 100 ^o C	mm ² /s	10	SRPS ISO 3104
Index viscosity	-	130	SRPS ISO 2909
Flash Point, COC	^o C	220	SRPS EN ISO 2592
Pour Point	^o C	-33	SRPS ISO 3016
Copper corossion , 3h, 100 ^o C	rating	1	SRPS ISO 2160

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight. Recommended storage temperature: max. 40°C

Packaging

<i>0.1L</i>	<i>0.25L</i>	<i>0.5L</i>	<i>1L</i>	<i>4L</i>	<i>10L</i>	<i>60L</i>	<i>180KG</i>	<i>850KG</i>	<i>IBC</i>	<i>AC</i>
				X4	X2		X	X		