

NISOTEC UNIVERSAL SAE 15W- 40, SAE 20W-50

NISOTEC UNIVERSAL is mineral universal, multigrade motor oil, viscosity grade SAE 15W-40 and SAE 20W-50, intended for the lubrication of gasoline and diesel engines of older, classic design of passenger car and light commercial vehicles and agricultural machinery working under moderate load. In relation to the standard mineral engine oil provides:

- Improved protection against wear and corrosion of engine parts
- Extended service life thanks to reduced engine deposits appear
- Easy start under all weather conditions

Performance Levels: API CF/SG/SF, ACEA E2

Characteristics

Properties	Units	Typical Values		Methods
		SAE 15W-40	SAE 20W-50	
Density at 15°C	g/cm ³	0,88	0,89	SRPS EN ISO 3675
Kinematic viscosity at 100°C	mm ² /s	15	17.5	SRPS ISO 3104
Index viscosity	-	135	130	SRPS ISO 2909
Flash Point, COC	°C	215	225	SRPS EN ISO 2592
Pour Point	°C	-27	-21	SRPS ISO 3016
Base Number	mgKOH/g	10	10	SRPS ISO 3771
Foaming, max seq I/ II/ III	mL/mL	10/0, 50/0,10/0	10/0,50/0,10/0	SRPS ISO 6247

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight. Recommended storage temperature: max. 40°C

Packaging

0.1L	0.25L	0.5L	1L	4L	10L	60L	180KG	850KG	IBC	AC
			X16	X4	X2		X			