

NISOTEC UNIVERSAL SAE 20W- 60

NISOTEC UNIVERSAL SAE 20W-60 is universal, multigrade mineral engine oil, intended for the lubrication of both, four-stroke gasoline as well as diesel engines of passenger car and light duty commercial vehicle of older design that have crossed many miles and have higher oil consumption. Features and Benefits:

- Good lubrication and wear protection
- Reliable engine operation under normal service conditions

Performance Levels: API CF/SG

Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Density at 15°C	g/cm ³	0.89	EN ISO 3675
Kinematic viscosity at 100°C	mm ² /s	23	ISO 3104
Apparent viscosity, CCS, at -15°C	mPa s	9200	ASTM D5293
Index viscosity	-	135	ISO 2909
Flash Point, COC	°C	230	EN ISO 2592
Pour Point	°C	-21	ISO 3016
Base Number	mgKOH/g	7.5	ISO 3771
Foaming, max seq I/ II/ III	mL/mL	10/0,50/0,10/0	ISO 6247

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight. Recommended storage temperature: max. 40°C

Packaging

<i>0.1L</i>	<i>0.25L</i>	<i>0.5L</i>	<i>1L</i>	<i>4L</i>	<i>10L</i>	<i>60L</i>	<i>180KG</i>	<i>850KG</i>	<i>IBC</i>	<i>AC</i>
			X16	X4			X			