


NISOTEC ANTIFRIZ G12 LONG LIFE 40

NISOTEC ANTIFRIZ G12 LONG LIFE 40 is an monoethylene glycol based fluid without phosphates, silicates, borates, amines and nitrites. It belong group of OAT (**O**rganic **A**cid **T**echnology) antifreeze. It provides protection against freezing and boiling but also protect engines cooling system against corrosion whether it is made from cast iron or aluminium. **It is ready mix product.** Features and Benefits:

- Excellent corrosion protection, rust and cavitation
- Aluminium protection
- Durability of cooling systems sealing materials and guts
- Long change interval-durability in cooling system 5 years

Performance Levels: SRPS H.Z2.010 tip III, organski, BS 6580, ASTM D3306, AFNOR NF R 15-601, VW/Audi/Skoda TL- 774D/F (G12/G12+), MB 326.3, MAN 324-SNF, Ford WSS-M97B44-D/E, GM 6277M (+B040 1065), Volvo Penta/Trucks, Deutz DQC CB-14, DAF 74002

Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Density at 20°C	g/cm ³	1.060	ASTM D5931
Color	-		Visually
pH value	-	8.2	ASTM D1287
Reserve alkalinity	mL HCL N/10mL	3	ASTM D1121
Boiling point, min.	°C	108	ASTM D1120
Foaming properties, max.	mL/s	50/5	ASTM D1881
Freezing point, max.	°C	-37	ASTM D1177

Storage and handling instructions

Follow storing and handling instructions given in SDS. Store in the original container in dry, properly ventilated area. Protect from direct atmospheric influences.

Packaging

<i>0.5L</i>	<i>1L</i>	<i>2L</i>	<i>4L</i>	<i>60L</i>	<i>210KG</i>	<i>IBC</i>
	X9				X	X