

NISOTEC TESTEROL

NISOTEC TESTEROL is chain-saw lubricating oil. It is a reliable lubricant intended for lubricating all types of chain saws used for woodworking in severe conditions, at high temperatures, in the presence of water, dust and mud. It should not be used for making the fuel mixture for chainsaws instead of two stroke engines oil. Features and Benefits:

- High antiwear properties of the chain elements
- Good adhesion
- Excellent anti-corrosion properties
- Effective separation of water
- Long life of chains-saw
-

Performance Levels: SRPS ISO 6743-1 (L-AC), Manufacturing specification SP-04.07.65-306

Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Density at 15 ^o C	kg/cm ³	0,887	SRPS EN ISO 3675
Kinematic viscosity at 40 ^o C	mm ² /s	98	SRPS ISO 3104
Flash Point, COC	^o C	220	SRPS EN ISO 2592
Pour Point	^o C	-21	SRPS ISO 3016
Copper corosion, 3h, 100 ^o C	mark	1a	SRPS ISO 2160

Storage and handling instructions

Store in the original container. Protect from direct atmospheric influences. Follow storing and handling instructions given in SDS.

Packaging

<i>0.1L</i>	<i>0.25L</i>	<i>0.5L</i>	<i>1L</i>	<i>2L</i>	<i>4L</i>	<i>10L</i>	<i>60L</i>	<i>180KG</i>	<i>IBC</i>	<i>AC</i>
			X16		X4	X2		X		